



***UNDER-THE-SINK
WATER FILTRATION SYSTEMS***

INSTALLATION INSTRUCTIONS
Models MFS10, MFS20, MFS30 & MFS40

AquaLink

This box contains:

- (1) 2 meter water pipe
 - (2) 1 connector
 - (3) 1 connector O-ring
 - (4) 1 ball valve
 - (5) 2 safety rings
 - (6) 1 faucet
 - (7) 1 faucet base
 - (8) 1 rubber ring
 - (9) 1 plastic ring
 - (10) 1 metal teeth ring
 - (11) 1 small nickel nut
 - (12) 1 plastic sleeve
 - (13) large nickel nut
 - (14) 1 plastic insert
- Filter holder(s), filters
and screws according to
the purchase.



Items not included in the box that you may need for installation:
Screw driver, bucket, Teflon tape for pipe connections, utility knife or
strong scissors, pliers, and adjustable wrench.

AquaLink



①



②



③



④



⑤

Place these items in the following order, in the appropriate place on top of the kitchen counter:
Rubber ring (8) → faucet base (7) → faucet (6).



⑥

Place these items in the following order under the kitchen counter:
Plastic ring (1) → teeth ring (10) → small nickel nut (11).



⑦

Connect the water pipe (1) to the faucet (6).



⑧

Place some Teflon tape on the connector (2) and on the ball valve (4).



⑨

Place the connector O-ring (3) into the connector (4).



⑩

Disconnect the cold water pipe of your kitchen and insert the connector (2) and the ball valve (4). Finally reconnect the cold water pipe to the connector (2).

AquaLink



- 11 Install the filter holder with the filters inside the kitchen cabinet with the screws provided.



- 12 Cut the water pipe (1) in a way that it can easily reach the outlet (indicated by the OUT sticker) on the filter holder. Make sure the ends of the pipe are straight.



- 13 Push the water pipe (1) in the outlet as far as you can. Pull the pipe (1) to ensure it is secured. Secure the connection with the safety rings (5).



- 14 Take the nut on the ball valve and place it around the water pipe.



- 15 Connect the water pipe to the ball valve by pushing in. You may want to apply some soap on the water pipe to ease the procedure. Finally connect the other edge of the water pipe to the inlet of the filter holder following the same instructions as in steps 12 and 13.

***Run the water for 10 minutes prior to first use.
Enjoy pure, clean water!***